

Powerful.
Practical.
Preferred.



Concealite's H Series Remote Head fixtures are made of durable, impact-resistant steel housings with the highest light output on the market... **up to 200 Watts!** These interior remote fixtures are ideal where emergency lighting codes require expansive illumination such as large complexes, areas of assembly, or applications with high ceilings.

H Series Remote Head Fixtures

Aesthetics

For remote installations, our powerful, stand-alone H Series Remote Fixture heads are available. The H Series remote high-powered halogen lamps provide up to 100 watts output each, surpassing anything currently on the market, and allowing for 20-30 feet above ground wall or vertical support pillar installations.

Architectural Features

- The H Series remote fixtures are available in single or dual head units.
- Can be configured to operate from a wide variety of emergency and standard power sources.
- Heads are mounted to a custom plate with a gasket that fits a single gang electrical box.
- Heads come white and bronze as standard colors.
- Custom colors, finishes, and textures available.
- Unique high output, long life halogen lamps are available in 20, 35, 50, 75, and 100 Watts.
- Heads are available in both 12 VDC and 120 VAC.
- Heads are UL 924 listed.



Commercial Office Building



Single or Dual Head Remote Fixtures
Custom Paint Finishes Available

H Series Remote Heads

FIXTURE SCHEDULE	FIXTURE TYPE:	PROJECT NAME/REF:
APPROVAL:	LAMP TYPE:	PROJECT LOCATION:

Mounting

Units are designed for mounting to any flat wall surface in exterior or interior wet location environments.

Wiring

Route appropriate WP connections via WP junction box conduit raceway system.

LPM Option: Low Profile Mounting system, includes 18 inches of continuous leads.

Illumination

The adjustable heads are UL listed. Specially designed high-output halogen lamps are available in 20, 35, 50, 75, and 100 watts. Concealite provides free point-by-point layout service for code compliance. Contact your local Concealite representative for details.

Product Specifications

The H Series remote head shall be constructed from aluminum and have an electrostatic baked powder coat finish. The head will be equipped with a locking gasketed swivel and have 1/2" fitting at the end of the swivel with a lock nut to mate with a gasketed custom wall plate. The head shall be available with 20, 35, 50, 75, & 100 Watt high output halogen lamps. These lamps shall have a minimum 2000 hour lamp life. The head shall have polished aluminum reflector and a gasketed glass lens. The head shall have a separate UL924 listing. The head assembly shall be rated for NEMA 4X areas.

Limited Warranty

All Concealite equipment is guaranteed against defects in materials and workmanship by the manufacturer for a period of three years from date of shipment under normal operations and proper use. Correction of all defects shall be by replacement or repair (at our discretion) and shall constitute fulfillment of all manufacturer's obligations.

H Series Remote Heads

Backplate dimensions measure 4" H x 2 1/2" W



Available Remote Power Options


Note: To order DC central battery systems shown below, contact Concealite for more info.



12v DC Central Battery Unit

Completely self-contained
 Models operate for up to four hours
 Fully automatic solid-state charger
 Automatic battery protection (LVD)
 Models for loads up to 300 watts output
 Die-formed heavy 18 gauge steel cabinet
 Dual 120 or 277 VAC input, field selectable
 1-1/2 hours of light to an end battery voltage of 87-1/2% of normal voltage
 Listed to UL 924
 See Central Battery Systems cut sheet for more details.

Ordering Information



Note: These specifications are subject to change



202 Elk Street, P.O. Box 160
 Elkton, SD 57026
 Phone: (605)542-4444
 Fax: (605)542-3333
 www.concealite.com